INSTALLATION INSTRUCTIONS FOR 1562-477

For Wall Mount Fixture **U.S. Patent No.: D530, 850**

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .

MOUNTING THE FIXTURE

Installation (see fig.1)

1. Shut off the power at the circuit breaker and remove old fixture, including the mounting plate.
2. Thread the two mounting screws about 1/4" into the pre-drilled holes in the mounting plate, spaced about the same distance apart as the holes in the fixture back plate. Attach the mounting plate to the junction box using two junction box screws. The side of the mounting plate marked "GND" must face out.
3. Follow wiring instructions carefully (see fig.2)
4. Mount fixture by aligning mounting holes in fixture back plate with mounting screws and threading ball nuts (A) onto mounting screws.
5. Place the socket sleeve (C) over the socket (B).
6. Install the light bulbs in accordance with the fixture's **specifications. DO NOT EXCEED THE MAXIMUM** WATTAGE RATING!
7. Clip the cloth shades (D) on to the bulbs.

Wiring (see fig.2)

1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the mounting plate.
2. Tuck the wire connections neatly into the wall junction box.

Fig.1



Fig.2


FIXTURE WIRES Black or Smooth
HOUSE WIRES Black (Hot)
FIXTURE WIRES White or Ribbed
HOUSE WIRES White (Neutral)
FIXTURE WIRES Bare Copper (Ground)
HOUSE WIRES Green or Bare Copper (Ground)

UL® Listed

american lighting association